

The Update of Fukushima Daiichi NPS


Agency for Natural Resources and Energy METI

25th February, 2020

1. The Mid-and-Long-Term Roadmap

- Decommissioning of Fukushima Daiichi NPS will be done by TEPCO in its responsibility.
- The decommissioning is an **unprecedented work with technical challenges**. **The Government of Japan has been taking initiative based on the Mid-and-Long-Term Roadmap**, with the target of the completion of decommissioning in 30-40 years in a safe and steady manner.

Time flame for Fukushima Daiichi Decommissioning



Role of the Government of Japan

GOJ sets the Roadmap

- The Inter-Ministerial Council for Contaminated Water and Decommissioning Issues has set out the Roadmaps.
 (Chairman: Chief cabinet secretary, First version: Dec. 2011)
- Revised for five times to date (Revised in July 2012, June 2013, June 2015, Sept. 2017, Dec. 2019)

 Based on the "Roadmap", mid-and long-term measures has been undertaken while giving top priority to the safety and keeping the attitude to value the risk reduction.

2. Key points of the revised "the Mid-and-Long-Term Roadmap"

Setting out a basic principle of "coexistence of reconstruction and decommissioning", while there has been gradual progress of residents' return and reconstruction efforts in surrounding area. (giving priority on early risk reduction and ensuring safety)

- Coexist with local communities.
- Optimize the whole decommissioning tasks", by reviewing the work process of 10 years.

• Total period of decommissioning is unchanged: "within 30-40 years"

(1) Fuel debris retrieval

Determine first implementing Unit and the method for fuel debris retrieval. Start trial retrieval at Unit 2 within 2021, by partial submersion method and side access The scale of the retrieval will be gradually enlarged.

(2) Fuel removal from pool

Change in the methods to suppress the dust dispersion at Unit 1 and 2 Postpone fuel removal for 4-5 years at Unit 1, and for 1-3 years at Unit 2 Aim at the completion of fuel removal from all Units 1-6, within 2031

(3) Contaminated water management

 The volume of contaminated water generated has been significantly suppressed. (540m³/day (May 2014) → 170m³/day (average of FY2018))



Keep current target of reducing the contaminated water generation to 150m³/d within 2020.
Set new target of reducing the contaminated water generation to 100m³/d within 2025.

* Handling of ALPS treated water will be continuously discussed in a comprehensive manner


3. Major milestones of Mid-and-Long-Term Roadmap (Dec. 2019)

Dec. 2011 Nov.	2013	Now Dec. 2021	End of 2	2031	30~40 years after cold shutdown
	Y				Hold
Phase 1	Phase 2	Phas	e 3-(1)	Phase 3	
Period until start of fuel removal (within 2 years)	Period until start of fuel debris r (within 10 years)		Period until completion of decommissioning (30-40 years later)		

Major milestone	S Ro	oadmap (Sept. 2017)	Revised Roadmap	
Contaminated water management	Reduce to about 150 m ³ /day Further reduction of generation	Within 2020	Within 2020 <u>Within 2025</u>	<u>NEW</u>
Stagnant water	Complete stagnant water treatment in buildings*	Within 2020	Within 2020(*)	
treatment	Reduce the amount of stagnant water in buildings to about a half of that in the end of 2020	-	<u>FY2022 - 2024</u>	<u>NEW</u>
	Complete of fuel removal from Unit 1-6	_	Within 2031	NEW
	Complete of installation of the large cover at Unit 1	-	Around FY2023	NEW
Fuel removal	Start fuel removal from Unit 1	Around FY2023	<u>FY2027 – 2028</u>	<u>REVISED</u>
	Start fuel removal from Unit 2 prevent dust scattering	Around FY2023	<u>FY2024 - 2026</u>	<u>REVISED</u>
Fuel debris retrieval	Start fuel debris retrieval from the first Unit (Start from Unit 2, expanding the scale gradually)	Within 2021	Within 2021	
Waste management	Technical prospects concerning the processing/disposal policies and their safety	Around FY2021	Around FY2021	
	Eliminating temporary storage areas outside for rubble and other waste	_	Within FY2028	<u>NEW</u>

* Excluding the reactor buildings of Units 1-3, process main buildings, and High temperature incineration building.


(Ref. 1) Current status of Unit 1-4 of Fukushima Daiichi NPS



<Dismantling of Unit 1/2 exhaust stack >




<Fuel debris retrieval>



the deposit likely to be the fuel debris was able to be gripped and moved. (Unit 2) [Feb. 2019]


<Fuel removal>



Started fuel removal from the spent fuel pool by remote control, for the first time from a nuclear reactor with core melt (Unit 3) [Apr. 2019]

[Ref.2] Impact on the Surrounding Environment


• The environmental impact on the site and surrounding area have been significantly reduced.



5

4. Generation of contaminated water, purification process and tank storage

- > Water gets contaminated when it touches the damaged reactors and fuel debris in buildings.
 - The level of groundwater outside is controlled to be higher than that of contaminated water inside the buildings to prevent the water flowing out of the building.
 - Groundwater keeps flowing into the buildings
- > TEPCO has been successful in removing most of radionuclides except tritium from contaminated water.
 - > ALPS (Multi-nuclide retrieval equipment) and the other equipment have been used. > See more at P8
- It is ALPS treated water, NOT -contaminated water, that is stored in the tanks.
 Radioactive materials in ALPS treated water are reduced to about 1/1,000,000 (one millionth).



5. Key figures of ALPS treated water



- ※ About 2 years will be needed for preparation and permission for disposal.
- $\ensuremath{\ensuremath{\mathbb{X}}}$ There is a limited room for further tank construction

Amount of Tritium (tritiated water) in tanks	Approx. 860 TBq* (16g) (*TBq = 1×10 ¹² Becquerel)
Average Concentration of Tritium	0.73 MBq/L (*MBq = 1×10 ⁶ Becquerel)

X As of Oct 31,2019

- %Currently, several kinds of radionuclides other than tritium are found in ALPS treated water in tanks. \rightarrow See page 8
- % If the treated water is discharged into the environment, it will be repurified and diluted to meet the standards for discharge.

Key Figures for ALPS treated water at the site (As of Dec 12, 2019)			
Number of tanks	965		
Tank Storage volume	About 1.18 million M		
Planned capacity (Under current plan)	About 1.37 million m ³ (by the end of 2020)		
Annual increase of ALPS treated water	About 50,000~60,000㎡/year		

Time to reach its full capacity (forecast): around summer of 2022

6. Characteristics of ALPS treated water

Two regulatory standards:


1) Applicable to storage: to keep site boundary dose levels less than 1mSv/year


Goal currently achieved through ALPS

- 2) Applicable to release to the environment: to keep radionuclides concentrations of treated water less than the regulatory limit.
- There are various concentration of ALPS treated water in the tanks, because:
 - Concentration of ALPS treated water depends on the attributes of water to be treated and operation management of ALPS such as frequency of absorbent exchange; and
 - Especially in the first few years after the accident, which was before improvement of ALPS performance, concentrations of tritium in ALPS treated water was relatively high.

In case of releasing ALPS treated water to the environment, the water needs to satisfy standard 2).

- TEPCO announced to re-purify ALPS treated water, to meet standard 2) for radionuclides other than tritium.
- ✓ After the re-purification, the water will be diluted to meet the standard 2) for tritium.





Sum of the ratios of actual concentrations to regulatory

*This is due to change of water level setting of full tanks. Treated water in this range (5-10 time) has not actually been added.


*These drawings are quoted from "Treated water `portal site(TEPCO HP)"

7. Process ahead

Role of the subcommittee:

1) to examine in a comprehensive manner, such as countermeasures for reputational damage, and 2) to compile report for the government

GOJ will decide its basic policy, after receiving report of subcommittee and discussing with parties concerned.



- <u>Reputational damage still remains and affects reconstruction of</u> <u>Fukushima.</u>
- "Coexistence of reconstruction and decommissioning" is a basic principle:
 - Returning of residents and reconstruction efforts in the surrounding area have been proceeding.
 - Additional reputational damage should not be caused by a hastened disposition of ALPS treated water.
- Disposition of ALPS treated water needs to be completed until the completion of the decommissioning:
 - with necessary storage, and
 - with due consideration to the minimization of the impact on reputation
- In deciding the disposition of the ALPS treated water, the government must also compile a policy for countermeasures against reputational damage.

9. The key points of the report (2): disposal methods

- <u>Vapor release and Discharge into the sea</u> have been conducted and recognized as feasible methods.
- There are precedents for <u>discharge into the sea</u> in Japan and it is easy to operate necessary facilities. Thus this <u>can be conducted with certainty</u>.
- Radiation impact of both methods is considerably small compared to natural exposure to radiation.

	Vapor release	Discharge into the sea
Technical Issues	 Precedent in case of accident at NPP overseas Vapor is also released from reactors in normal operations at the time of ventilation. In Japan, there is no example of vapor release in order to dispose liquid waste. Difficult to predict how the released vapor is diffused into the air Difficult to establish proper monitoring methods 	 Precedents exist world-wide More reliable option precedents in Japan and easiness of operating facilities Relatively easy to predict how discharged water is diffused in the ocean Easy to examine proper monitoring method
Social	 Difficult to compare the social impacts of two methods * Social impact is greatly dependent on consumer psychology. 	
issues	 May attract significant social concern 	 May attract particularly large social concern if no countermeasure for reputational damage is taken

The following three options have many insurmountable issues (regulatory, technological, and timewise) Geosphere injection : Need to seek for appropriate sites, and monitoring methods have not been established

Hydrogen release : Further technological development would be required for pretreatment and scale expansion.

Underground burial : In solidification process, water including tritium will be evaporated. New regulations may be necessary. Area for disposal yard will be needed.

[Ref. 3] Impact assessment for environmental release of ALPS treated water

[Conditions]

 Using UNSCEAR^{*1} assessment model^{*2} and precondition that all the treated water stored in tanks (containing 860TBq of tritium) is discharged in one year.

(*1: UNSCEAR: The United Nations Scientific Committee on the Effects of Atomic Radiation)

(*2: re-assessed with Japanese food consumption)

[Ref. UNSCEAR 2016 Report, Annex A "Methodology for estimating public exposures due to radioactive discharges"]

[case 1] Vapor release ----- Approx. **0.0012 mSv/year** (1.3 μSv/year)

[case 2] Discharge into the sea ---- Approx. 0.000071 to 0.00081 mSv/year (0.071 to 0.81 µSv/year)


In both discharge methods, <u>the impact of the radiation from the discharge is considerably small</u>, <u>compared with annual natural exposure in Japan: 2.1 mSv/year</u> (2,100 μSv/year).

Exposure dose [mSv/y]	Vapor release ^{%1}	discharge into the sea ^{%2}
All radionuclides ^³	0.0012 ^{※4}	0.000071~0.00081
- tritium	0.0012	0.000068

%1 Sum of external dose from the atmosphere and soils, and internal dose from inhaling the air and ingesting terrestrial life (at 5km points from the FDNPS)%2 Sum of external dose from beaches and internal dose from ingesting marine life.

X3 Estimation was conducted on the two assumptions that "ND (Not Detected)" nuclides are 1) their ND value and 2) zero.

%4 For exposure dose for [case 1 (vapor release)], there is no difference between the results from two assumptions



10. The key points of the report(3): Countermeasures against reputational damage

- 1) Well planned disposition process
- 2) Expansion and enhancement of countermeasures building on best practices
- 3) Continuous and flexible response

<1. Well planned disposition processes >

- <u>Re-purify</u> radionuclides other than tritium
- Stop the disposition process in case of emergency

e.g. environmental situation, malfunction of facilities

Determine the details (starting time, volume, and period of disposition), while listening to opinions of stakeholders

Disseminate information in a considerate and an easy-to-understand manner

- Concentration of pre-disposition ALPS treated water
- ✓ Monitoring results of surrounding environment

Explain safety of surrounding environment by utilizing diffusion simulation

<2. Expansion and enhancement of countermeasures building on best practices>

< Risk communication>

- to convey relevant information
- <u>Disseminating information</u> on the disposal method and scientific knowledge in advance

Providing information via:

- Social media, mass media
- ✓ On-site lectures

Strengthening information dissemination abroad

- ✓ Basic information on decommissioning
- Disposition methods in the world as well as precedents outside of Japan

< Economic measures>

- for reputational damage

- <u>Constructing analytical framework</u> for:
 - \checkmark Environmental monitoring, and
 - ✓ Food sampling measurement
- Utilizing <u>third-party certification</u> to secure consumer trust, such as
 - ✓ GAP (Good Agricultural Practice)
 - ✓ MEL (Marine Eco-label)
- Developing new market channels by
 - Promotion events for Fukushima products
 - Allocation of special sales staff in stores
 - ✓ Opening of <u>on-line stores</u> etc.

[Ref. 4] Possibility of storage continuation

There is a limited room for construction of additional tanks.

(Tank capacity under the current plan: approx. 1.37 million m³)

- ✓ Areas where flanged tanks used to be built may become available.
- ✓ For further decommissioning work, various facilities will be needed (such as storage tanks for ALPS treated water temporary storage facilities for spent fuel and fuel debris).
- Entire premises should be used effectively, considering its limitation.



[Ref. 5] Storage at off-site

- If ALPS treated water would be stored at off-site,
 - Legally compliant transfer facilities would be required.
 - Consensus would be needed from the municipalities where a possible transfer route would be located.
 - At a storage site, operation license and approval of local municipalities would be needed.

→ The transfer of ALPS treated water to off-site would <u>require significant preparation a</u> wide range of coordination in advance and considerable period of time.

[Issues on transfer to off-site]

- Transfer facilities in accordance with the laws and regulations would be needed.
 - ex. **Pipeline**: physical protection facilities (fence, etc.) surrounding the pipelines would be needed.
 - ex. Vehicles or ships: need to carry type L transport casks (maximum volume of 4 m³) procedure for transport outside the nuclear site would be needed.
- Consensus would be needed from local municipalities where a possible transfer route would be located.
- Leakage risk during transfer cannot be ruled out.

[Issues on off-site storage]

- Operation license for a storage site in accordance with the laws and regulations.
- Consensus from local municipalities at the storage site would be needed.

[Ref. 6] Tritium separation technology

<u>Tritium separation</u> \rightarrow removing highly concentrated tritiated water (HCTW) from lowly concentrated tritiated water (LCTW).

- If the tritium separation technology would be applied to ALPS treated water, large amount of LCTW, which needs to be disposed of after dilution to meet the regulatory standards, would have to be generated.
- HCTW needs to be stored continually.
- Preceding cases of tritium separation technologies show that the application of the technologies to ALPS treated water is NOT practical because:
 - ✓ <u>The tritium concentration of ALPS treated water is too low to be applied to.</u> (See red boxes below)
 - ✓ <u>The throughput of existing separation technologies are too small to deal with ALPS treated water.</u>

(See green boxes below)


- Demonstration project for tritium separation technology (2014-2016) revealed that <u>there was</u> no technology close to practical use for ALPS treated water.
 - Technological trends should be monitored carefully and continuously.

 Table: Existing tritium separation technologies: the change of concentration and throughput

Preceding cases	Applied separation technologies	Concentration before separation/ raw water	Concentration after separation [LCTW]**	Throughput (m³/day)
Darlington Tritium Removal Facility (Canada)	Isotope exchange + Hydrogen distillation	0.4 ~ 1.3 TBq/L	0.01-0.035 TBq/L	8.6
Wolsong Tritium Removal Facility (Korea)	Isotope exchange + Hydrogen distillation	0.04∼2 TBq/L	0.001-0.07 TBq/L	2.1
Fugen Heavy Water Upgrader (II) (Japan)	Isotope exchange	0.1 TBq/L	0.000004 TBq/L (4 MBq/L)	0.03
ITER Tritiated Water Treatment Equipment (Design stage) (EU)	lsotope exchange+ Hydrogen distillation	0.4 TBq/L [*]	0.000004 TBq/L (4MBq/L)	0.48 [*]
(Ref.) ALPS treated water at FDNPS	-	0.00000073 TBq/L (0.73 MBq)	-	At least, several hundreds m³/day
*The data is only from isotope exchange.	**The above figures of tri	tium concentration are the on	es before dilution for discharge.	17

11. The key of the report(4): Examples of tritium emission

[Ref.]Annual Tritium emissions from nuclear facilities around the world



Other countries : UNSCEAR 2008 Annual report J Japan : Fukushima Pref. and TEPCO report 2010 (data period from April 1, 2010 to March 11, 2011)


References

[Ref.7] Decommissioning of TEPCO Fukushima Daiichi NPS (FDNPS)

◇ Fukushima Daiichi Decommissioning is a continuous risk reduction activity to protect the people and the environment from the risks associated with radioactive substances by:

- ✓ Removing spent fuel and fuel debris from the Reactor Building
- ✓ Reducing the risks associated with <u>contaminated water</u> and <u>radioactive waste</u>

Safe and steady decommissioning is a prerequisite for reconstruction of Fukushima



[Ref. 8] What is Tritium?

Tritium is a relative of hydrogen that emits weak radiation.

> Tritium exists naturally and is found in water such as water vapor in the atmosphere, rain, sea water, and tap-water, as tritiated water has similar properties as those of water.

It has not been found that tritium concentrates in human beings and particular living organisms


Impact on health is very low, around 1/300 of that of Potassium-40.

(* Potassium-40 is abundant in foods such as vegetables and fruits.)

NPPs in Japan and overseas have been discharging water containing tritium for more than 40

years in compliance with the standard limits based on the laws and regulations.

- Concentration of tritium in sea water near NPPs are significantly lower than that of drinking water standards in the world.
- <u>It has not been found that tritium from NPPs have an impact on health.</u>
- The amount of tritium, which is generated at domestic nuclear power plants (NPPs) and released into the sea annually*, is around <u>1.7 times as much as that of tritium found in annual precipitation in Japan</u>. (* 5 year average before 2011)



[Ref. 9] Impact assessment –UNSCEAR Model* -

UNSCEAR Model*

- Made for public exposure assessment in the case of radionuclides discharge, both to the air and into the sea, on the assumption that there has been constant discharge**.
 - * Re-assessment was made using national health and nutrition examination survey in Japan.
 - ** assess the public exposure in the 100th year, on the assumption that there will be a continuous and constant discharge for 100 years

[Case 1] Vapor release

- Public exposure is calculated as the sum of external dose from the atmosphere and soil, and internal dose from inhaling the air and ingesting terrestrial life (at 5km points off the leeward side of the FDNPS).
 - Rate of the time staying outside: 0.2
 - Rate of the local terrestrial food: 0.25
 - Amount of Food consumption per person (kg/year): Japan (Ref: Asia+Pacific) (Grains 155 (141.5), Plants/Fruits 188 (240.8), Mild/Dairy products 41.8 (44.5), Meat/Internal organs 35.4(29.5))

[Case 2] Discharge into the sea

- > Public exposure is calculated as the sum of external dose from beaches and internal dose from ingesting marine life.
- For the assessment, sea area is divided into local sea areas (area with 1 billion m³ of sea water) and regional sea area (with 1000 trillion m³)
 - Rate of marine food from local sea area: Fish 0.25, Crustacea 1.0, Mollusk 1.0
 - Rate of marine food from regional sea area: Fish 0.75, Crustacea 0, Mollusk 0
 - Amount of Food consumption per person (kg/year): Japan (Ref: Asia + Pacific) (Fish 21.7 (6.9), Crustacea 1.42(1.4), Mollusk 1.97 (2.4))

Other parameters for the assessment

- Assumption of concentration of tritium before dilution : 1 M Bq/L (concentration rate will be set to meet the standard before discharge)
- Concentration of radionuclides other than tritium before dilution: Data of the treated water stored in K4 tank area**
 (** Radionuclides that are not detected (ND) is assumed to be 1) their ND value and 2) zero, ¹⁴C = 10Bq/L)

[Ref.10] Information Portal site (1) : Fukushima Daiichi NPS



Decommissioning and Contaminated Water Management at TEPCO's Fukushima Daiichi NPS

https://www.meti.go.jp/english/earthquake/nuclear/dec ommissioning/index.html

- Film, Fukushima Today 2019
 - Efforts to Decommission and Reconstruction https://www.youtube.com/watch?v=v_PeSp--Wuk
- Film, Fukushima Today
 - 8 years after the earthquake -

https://www.youtube.com/watch?v=pKjsSAz5Kws









Treated Water Portal Site


http://www.tepco.co.jp/en/decommission/progress/watertreatment /index-e.html

Observation Data, Fukushima Daiichi NPS

https://www7.tepco.co.jp/responsibility/decommissioning/1f_newsr oom/data/index-e.html







Fukushima Daiichi Status Updates

ernational Atomic Energy Agency

https://www.iaea.org/newscenter/focus/fukushima/status-update

IAEA Review mission reports (Press release)

IAEA Team Completes Fourth Review of Japan's Plants to Decommission Fukushima Daiichi (November 13, 2018) https://www.iaea.org/newscenter/pressreleases/iaea-team-completes-fourth-review-

of-japans-plans-to-decommission-fukushima-daiichi

IAEA Issues Final Report on Fourth Review of Fukushima Decommissioning (January 31, 2019) https://www.iaea.org/newscenter/pressreleases/iaea-issues-final-report-on-fourthreview-of-fukushima-decommissioning



United Nations Scientific Committee on the Effects of Atomic Radiation

UNSCEAR 2016 REPORT -Sources, effects and risks of ionizing radiation

hhttps://www.unscear.org/unscear/en/publications/2016.html





